

In re Patent Application of:
DE LAENDER ET AL.
Serial No. 10/660,067
Confirmation No. 6186
Filed: September 11, 2003
_____ /

In the Claims:

Claims 1-63 (Cancelled).

64. (Previously Presented) A pallet comprising:

a top support member for supporting cargo;

a bottom support member;

a plurality of solid support blocks for separating the top and bottom support members so that a lifting member can be inserted ~~therebetween~~; therebetween, at least one of the support blocks comprising first and second substantially flat surfaces located on opposite ends of a longitudinal axis, third and fourth substantially flat surfaces between the opposite ends of the longitudinal axis, and curved surfaces between the first and third flat surfaces, between the first and fourth flat surfaces, between the second and third flat surfaces and between the second and fourth flat surfaces;

each solid support block comprising a composite material entirely devoid of any openings and comprising at least one cellulose ~~cellular~~ material and at least one thermoplastic material, and having upper and lower support member fastening surfaces for defining respective upper and lower support member fastener areas; and areas, the at least one thermoplastic material comprising polyethylene having a density between about 0.9 grams per cubic centimeter and about 0.98 grams per cubic centimeter; and

In re Patent Application of:

DE LAENDER ET AL.

Serial No. 10/660,067

Confirmation No. 6186

Filed: **September 11, 2003**

a plurality of fasteners fastening the top and bottom support members to the plurality of solid support blocks via the respective upper and lower support member fastener areas.

65. (Previously Presented) The pallet according to claim 64, wherein the plurality of solid support blocks comprises three groups of blocks, wherein a first group of support blocks is positioned in a first row adjacent a first edge of the pallet, a second group of support blocks is positioned in a second row across the center of the pallet, and a third group of support blocks is positioned in a third row adjacent a second edge of the pallet.

66. (Previously Presented) The pallet according to claim 65, wherein the first, second and third rows are positioned substantially parallel to each other.

67. (Previously Presented) The pallet according to claim 65, wherein the top support member comprises:

three cross supports positioned generally parallel to each other, wherein the first, second, and third rows of support blocks support the three cross supports; and

at least one plate coupled to a top surface of the three cross supports.

Claims 68-69 (Cancelled).

In re Patent Application of:
DE LAENDER ET AL.
Serial No. 10/660,067
Confirmation No. 6186
Filed: **September 11, 2003**

70. (Currently Amended) The pallet according to claim 64 ~~claim 68~~, wherein the polyethylene is selected from the group consisting of a linear low density polyethylene, an ultra low density polyethylene, a low density polyethylene, a high density polyethylene, and an ultra high molecular weight polyethylene.

Claims 71-72 (Cancelled).

73. (Currently Amended) The pallet according to claim 64, wherein the cellulous ~~cellular~~ material has particles sizes between about 0.1 mm and about 1 mm.

Claim 74 (Cancelled).

75. (Currently Amended) The pallet according to claim 64, wherein the cellulous ~~cellular~~ material is selected from the group consisting of wood, linen flax shives, bagasse from sugar cane, jute, rice husks, paper fiber, recycled ~~recycles~~ paper, nut shells, cornhusks, and bamboo.

Claims 76-79 (Cancelled).

80. (Currently Amended) The pallet according to claim 64, wherein the at least one cellulous ~~cellular~~ material includes particle sizes between about 0.05 mm and about 4 mm.

In re Patent Application of:

DE LAENDER ET AL.

Serial No. **10/660,067**

Confirmation No. **6186**

Filed: **September 11, 2003**

81. (Currently Amended) The pallet according to claim 64, wherein a concentration of the cellulose ~~cellular~~ material in the composite is between about 40 percent and about 60 percent.

82. (Currently Amended) A pallet comprising:

a top support member comprising a plurality of spaced apart cross supports positioned generally parallel to each other, and at least one plate coupled to an upper surface of said plurality of spaced apart cross members for supporting cargo;

a bottom support member;

a plurality of ~~oval-shaped~~ solid support blocks for separating the plurality of cross supports and the bottom support member so that a lifting member can be inserted ~~therebetween;~~ therebetween, at least one of the support blocks comprising first and second substantially flat surfaces located on opposite ends of a longitudinal axis, third and fourth substantially flat surfaces between the opposite ends of the longitudinal axis, and curved surfaces between the first and third flat surfaces, between the first and fourth flat surfaces, between the second and third flat surfaces and between the second and fourth flat surfaces;

each solid support block comprising a composite material entirely devoid of any openings and comprising at least one cellulose ~~cellular~~ material and at least one thermoplastic material, and having upper and lower support member fastening surfaces for defining respective upper and lower fastener areas; ~~and area,~~ the at least one thermoplastic material comprising at

In re Patent Application of:

DE LAENDER ET AL.

Serial No. **10/660,067**

Confirmation No. **6186**

Filed: **September 11, 2003**

least one of homopolymers and copolymers having densities between about 0.8 grams per cubic centimeter and about 0.99 grams per cubic centimeter; and

a plurality of fasteners ~~nails~~ fastening the top and bottom support members to the plurality of solid support blocks via the respective upper and lower fastener areas.

83. (Previously Presented) The pallet according to claim 82, wherein the plurality of solid support blocks comprises three groups of blocks, wherein a first group of support blocks is positioned in a first row adjacent a first edge of the pallet, a second group of support blocks is positioned in a second row across the center of the pallet, and a third group of support blocks is positioned in a third row adjacent a second edge of the pallet.

84. (Previously Presented) The pallet according to claim 83, wherein the plurality of cross supports comprise at least three cross supports positioned generally parallel to each other, and wherein the first, second, and third rows of support blocks support the three cross supports.

Claims 85-86 (Cancelled).

87. (Currently Amended) The pallet according to claim 82, wherein the cellulous ~~cellular~~ material is selected from the group consisting of wood, linen flax shives, bagasse from sugar

In re Patent Application of:
DE LAENDER ET AL.
Serial No. 10/660,067
Confirmation No. 6186
Filed: **September 11, 2003**

cane, jute, rice husks, paper fiber, recycled ~~reeyeles~~ paper, nut shells, cornhusks, and bamboo.

88. (Currently Amended) The pallet according to claim 82, wherein a concentration of the cellulous ~~cellular~~ material in the composite is between about 40 percent and about 60 percent.

Claims 89-95 (Withdrawn).

96. (New) A pallet comprising:

a top support member for supporting cargo;

a bottom support member;

a plurality of solid support blocks for separating the top and bottom support members so that a lifting member can be inserted therebetween, at least one of the support blocks comprising first and second substantially flat surfaces located on opposite ends of a longitudinal axis, third and fourth substantially flat surfaces between the opposite ends of the longitudinal axis, and curved surfaces between the first and third flat surfaces, between the first and fourth flat surfaces, between the second and third flat surfaces and between the second and fourth flat surfaces;

each solid support block comprising a composite material entirely devoid of any openings and comprising at least one cellulous material and at least one thermoplastic material, and having upper and lower support member fastening surfaces for defining respective upper and lower support member fastener

In re Patent Application of:
DE LAENDER ET AL.
Serial No. 10/660,067
Confirmation No. 6186
Filed: September 11, 2003

areas, the at least one thermoplastic material comprising at least one of polyesters, epoxies and vinyl esters; and

a plurality of fasteners fastening the top and bottom support members to the plurality of solid support blocks via the respective upper and lower support member fastener areas.

97. (New) The pallet according to claim 96, wherein the plurality of solid support blocks comprises three groups of blocks, wherein a first group of support blocks is positioned in a first row adjacent a first edge of the pallet, a second group of support blocks is positioned in a second row across the center of the pallet, and a third group of support blocks is positioned in a third row adjacent a second edge of the pallet.

98. (New) The pallet according to claim 97, wherein the first, second and third rows are positioned substantially parallel to each other.

99. (New) The pallet according to claim 97, wherein the top support member comprises:

three cross supports positioned generally parallel to each other, wherein the first, second, and third rows of support blocks support the three cross supports; and

at least one plate coupled to a top surface of the three cross supports.

In re Patent Application of:

DE LAENDER ET AL.

Serial No. **10/660,067**

Confirmation No. **6186**

Filed: **September 11, 2003**

100. (New) The pallet according to claim 96, wherein the cellulous material has particles sizes between about 0.1 mm and about 1 mm.

101. (New) The pallet according to claim 96, wherein the cellulous material is selected from the group consisting of wood, linen flax shives, bagasse from sugar cane, jute, rice husks, paper fiber, recycled paper, nut shells, cornhusks, and bamboo.

102. (New) The pallet according to claim 96, wherein the at least one cellulous material includes particle sizes between about 0.05 mm and about 4 mm.

103. (New) The pallet according to claim 96, wherein a concentration of the cellulous material in the composite is between about 40 percent and about 60 percent.